

H170110



*Cyanosis compliant on request




Key Features


- Even light distribution
- Complies with relevant Australian Standards
- Diverse possibilities
- SELV LED Engine
- Screwless end caps (On Request)
- Emergency Options (On Request)
- Manufactured in Australia

Dimensions

Profile



Colour Options



Mounting

Surface Mounted (S) Wall Up & Down Mounted (C) Wall Mounted (W)



Code

Example: H170110 - W129030ODDO10 - 2400

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length												
H170110	S	12	12 W/m	1020 lm/m	80	CRI>80	30	3000K	OD	Opal	DO	Non-Dim	10	Black	- XXXX					
	W	16	16 W/m	1360 lm/m									90	CRI>90		35	3500K	DA	DALI	11
	C	Wall Up/Down	20	20 W/m	1700 lm/m									75		Grey				
			24	24 W/m	2040 lm/m									50		5000K	CA	Casambi	79	Anodised
			28	28 W/m	2380 lm/m									TW		Tunable White	T2	Tunable White	CU	Custom
			32	32 W/m	2720 lm/m															
			36	36 W/m	3060 lm/m															
			40	40 W/m	3400 lm/m															
			44	44 W/m	3740 lm/m															
			48	48 W/m	4080 lm/m															

FOS Lighting reserve the right to change any data without notification