


HYPER 2.3



Key Features

- 5 Year Warranty
- CRI>90 or CRI>97
- IP20 (from below)
- Honeycomb or frosted filter options

Dimensions



Technical Information

LED Output	Module Output	Beam Angle	Height (H)	Diameter (D)	Cut Out	2700K CRI>97*	3000K CRI>97*	4000K CRI>97*
4W	5W	18°, 25°, 40°, 60°	60mm	125mm	92mm	418lm	428lm	474lm
9W	10W	18°, 25°, 40°, 60°	60mm	125mm	92mm	871lm	891lm	987lm
13W	15W	18°, 25°, 40°, 60°	60mm	125mm	92mm	1145lm	1186lm	1322lm
18W	20W	18°, 25°, 40°, 60°	80mm	125mm	92mm	1603lm	1686lm	1922lm

* Lumens based on 40 degree beam angle

Code

Example: **Hyper 2.3-4W-B-27K-18-90-STD-HC**

Fitting	Wattage		Frame Colour		LED Colour		Beam Angle		CRI		Dimming		Filters	
Hyper 2.3	4W	4W	B	Black	27K	2700K	18	18°	90	CRI>90	STD	Trailing & Leading Edge Dim (Standard) DALI Dim	HC	Honeycomb Frosted
	9W	9W	W	White	3K	3000K	25	25°	97	CRI>97	DALI		FR	
	13W	13W			4K	4000K	40	40°						
	18W	18W					60	60°						

HAWKO Lighting reserve the right to change any data without notification