CEILING MOUNTED LOW TRIM DOWNLIGHT (100 SERIES)

IP65

5 YR WARRANTY

Key Features

- 5 Year Warranty
- CRI>80 (Standard), CRI>90 (Optional)
- 220-240V
- Working Temperature: -20°c to +50°c
- 2mm thick toughened glass diffuser
- Aluminium housing with corrosion resistant powdercoating
  L80 >50000 hours

Dimensions



Technical Information

	Dimensions	Illumination	Lumens
	Width (W) x Height (H)	Wattage	Lumens/m
CML100120	100mm x 120mm	1x5	577
		1x10	1152
CML100150	100mm x 150mm	1x5	577
		1x10	1152
		1x15	1725
CML100200	100mm x 200mm	1x5	577
		1x10	1152
		1x15	1725

Code

Example: CML100120-1x5W-3K-80-B-ND-12

Fitting	Mounted		Illumination		LED Colour		CRI		Finish		Control Gear		Beam Angle	
CML100120 CML100150 CML100200	S P	Suface Mounted Pendant	1x5W 1x10W 1x15W	1x5 Watts 1x10 Watts 1x15 Watts	3K 4K 6K	3000K 4000K 6000K	80 90	CRI>80 CRI>90	B W G M BR	Black White Grey Stainless Steel Mirror Stainless Steel Brushed	ND DA	Non-Dim DALI	12 24 36 60	12° 24° 36° 60°

HAWKO Lighting reserve the right to change any data without notification