

CEILING MOUNTED LOW TRIM DOWNLIGHT (120 SERIES)



IP65


5 YR WARRANTY



Key Features

- 5 Year Warranty
- CRI>80 (Standard), CRI>90 (Optional)
- 220-240V
- Working Temperature: -20°c to +50°c
- 2mm thick toughened glass diffuser
- Aluminium housing with corrosion resistant powdercoating
- L80 >50000 hours

Dimensions



Technical Information

	Dimensions	Illumination	Lumens
	Width (W) x Height (H)	Wattage	Lumens/m
CML120150	120mm x 150mm	1x10	1182
		1x15	1743
		1x20	2385
		1x25	2728
CML120200	120mm x 200mm	1x10	1182
		1x15	1743
		1x20	2385
		1x25	2728

Code

Example: CML120150-1x15W-3K-80-B-ND-12

Fitting	Mounting		Illumination		LED Colour		CRI	Finish		Control Gear		Beam Angle	
CML120150 CML120200	S	Surface Mounted	1x10W	1x10 Watts	3K	3000K	80	B	Black	ND	Non-Dim	12	12°
	P	Pendant	1x15W	1x15 Watts	4K	4000K	90	W	White	DA	DALI	24	24°
			1x20W	1x20 Watts	6K	6000K		G	Grey			36	36°
			1x25W	1x25 Watts				M	Stainless Steel Mirror			60	60°
								BR	Stainless Steel Brushed				

HAWKO Lighting reserve the right to change any data without notification