

HYPER 2.1

IP20


5
YR
WARRANTY



Key Features

- 5 Year Warranty
- CRI>90 or CRI>97
- IP20
- Adjustable LED downlight
- Honeycomb or frosted filter options

Dimensions



Technical Information

	Beam Angle	Height (H)	Diameter (D)	Cut Out	2700K CRI>97	3000K CRI>97	4000K CRI>97
4W*	18°, 25°, 40°, 60°	60mm	93mm	80mm	418lm	428lm	474lm
9W*	18°, 25°, 40°, 60°	60mm	93mm	80mm	871lm	891lm	987lm
13W*	18°, 25°, 40°, 60°	60mm	93mm	80mm	1145lm	1186lm	1322lm
18W*	18°, 25°, 40°, 60°	80mm	93mm	80mm	1603lm	1686lm	1922lm

*Fitting Wattage
** Lumens based of 40 degree beam angle

Code

Example: Hyper 2.1-4W-B-27K-18-90-STD-HC

Fitting	Wattage		Frame Colour		LED Colour		Beam Angle		CRI		Dimming		Filters	
Hyper 2.1	4W 9W 13W 18W	4W 9W 13W 18W	B W S	Black White Siver	27K 3K 4K	2700K 3000K 4000K	18 25 40 60	18° 25° 40° 60°	90 97	CRI>90 CRI>97	STD DALI	Trailing & Leading Edge Dim (Standard) DALI Dim	HC FR	Honeycomb Frosted

HAWKO Lighting reserve the right to change any data without notification