

75 SQUARE - H7585




Key Features


- Minimum length 600mm
- Maximum module length 4m
- 45°, 90°, T, X, Y bends available
- IP55 (On request)
- 3.3kg/m
- Custom colours available on request
- L80 B10 >100K Hours Lifetime

Dimensions

Profile



Colour Options



Mounting

Surface Mounted (S) Wire Pendant (P) Recessed Trimless (T) Wall Mounted (W)
Rod Pendant (D) Wall Mounted Adjustable (A)



Code

Example: **H7585 - S168030ODD011 - 2400**

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
H7585	S Surface Mounted P Wire Pendant D Rod Pendant T Trimless Recessed W Fixed Wall A Adjustable wall	16 16W/m 1353 lm/m 19 19 W/m 1769 lm/m 26 26 W/m 2289 lm/m 35 35 W/m 3017 lm/m 40 40W/m	80 CRI>80 90 CRI>90	30 4000K 40 4000K 50 5000K TW 2700K - 6500K	OD MF Opal Micro Prismatic Frosted	DO Non-Dim DA DALI PD Push-Dim CA Casambi TW Tunable White	10 Black 11 White 75 Gray CU Custom	- XXXX

HAWKO Lighting reserve the right to change any data without notification

**Lumens based on 4000K

***CRI 80 as standard