


# 30 ANGLE - HE3030CR




## Key Features

- Easy installation
- Max module lengths are 2.5m
- Butt joins to create longer lengths
- 45 & 90 bends available (custom bends available upon request)
- Grey PMMA screwless end caps

## Dimensions

### Profile



## Colour Options



## Technical Information

ECO FLEX G2												
IP20/IP67												
CRI>80												
Heatsink required for installation												
4.8W/m (5)			9.6W/m (10)			14.4W/m (15)			19.2W/m (20)			
2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	
500lm/m	520lm/m	575lm/m	1000lm/m	1050lm/m	1150lm/m	1530lm/m	1630lm/m	1730lm/m	2050lm/m	2150lm/m	2300lm/m	

#See individual LED Flex data sheet for full break down

## Code

Example:

HE3030CR- S049027ODD079 - 2400

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
HE3030CR	S Surface Mounted	5 4.8W/m 10 9.6W/m 15 14.4W/m 20 19.2W/m	80 CRI>80	27 2700K 30 3000K 40 4000K	OD LED+	DO Non-Dim DA DALI CA Casambi PD Phase Dim	79 Anodised	- XXXX
OR HE3030CRIP								

# HAWKO Lighting reserve the right to change any data without notification