



Key Features

- Minimum bend diameter - 300mm
- Bending Direction - Vertical, Horizontal
- Remote Driver
- Direct or Side Entry
- Surface Mounted, Wire Suspended, Rod Suspended

Technical Information

	Wattage (W/m)	Lumens (Lm/m)	Max Run Length (m)	Incremental Order Length (mm)
Monochrome	16	850	5	33.3
RGB		320		62.5
RGBW		350		83.3

Lumens values based on 4000K, CRI>80

If this fittings needs to be adjusted on site, contact FOS Lighting before cutting the product.

Accessories

Wire Suspension (2500mm)



Rod Suspension (600mm)



Polycarbonate Clips



Polycarbonate Sleeve (250mm)



Code

Example: HTMB25-S-16-50-40-DE-D0-2500

Code	Mounting	Power	CRI	CCT	Connector	Driver	Length
HTMB25	HAWKO Tube multi bend 25mm diameter	16 16 W/m	80 CRI>80 90 CRI>90	27 2700K 30 3000K 40 4000K 60 6500K RGB RGB RGBW RGBW	DE Direct Entry SE Side Entry	D0 Non-Dim DMX DMX SPI SPI CA Casambi DA DALI-Dim SW Switch Dim	- XXXX

FOS Lighting reserve the right to change any data without notification