


36D - HE3640D




Key Features

- Dot free illumination with 120 LED/m strips
- Easy installation
- Max module lengths are 2.9m
- Butt joints to create longer lengths
- 2m adjustable wire suspensions when suspending the luminaire
- 45 & 90 bends available (custom bends available upon request)
- Aluminium screwless end caps

Dimensions

Profile



Colour Options



Technical Information

ECO FLEX G2												
IP20/IP67												
CRI>80												
Heatsink required for installation												
4.8W/m (5)			9.6W/m (10)			14.4W/m (15)			19.2W/m (20)			
2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	
500lm/m	520lm/m	575lm/m	1000lm/m	1050lm/m	1150lm/m	1530lm/m	1630lm/m	1730lm/m	2050lm/m	2150lm/m	2300lm/m	

#See individual LED Flex data sheet for full break down

Code

Example: HE3640D - S059027ODD011 - 2400

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length				
HE3640D	S P	Surface Mounted Wire Pendant	5 10 15 20	4.8W/m 9.6W/m 14.4W/m 19.2W/m	80 CRI>80	27 30 40 60	2700K 3000K 4000K 6000K	OD LED+	DO DA CA PD	Non-Dim DALI Casambi Phase Dim	79 Anodised	- XXXX
OR												
HE3640DIP												

HAWKO Lighting reserve the right to change any data without notification