

# 18 SLIM - H1807




## Key Features


- Dot free illumination with 120 LED/m strips
- Easy installation
- Max module lengths are 2.5m
- Butt joins to create longer lengths
- 2 clear mounting clips per metre of extrusion
- 45 & 90 bends available (custom bends available upon request)
- Grey PMMA screwless end caps

## Dimensions

Profile



Mounting Bracket



## Colour Options



## Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

# Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

## Code

Example: **H1807 - S049027ODDO79 - 2400**

Code	Mounting		Power		CRI		CCT		Optics		Driver		Finish		Length
H1807	S	Surface Mounted	04	4W/m	80	CRI>80	27	2700K	OD	Opal	DO	Non-Dim	79	Anodised	- XXXX
			08	8W/m	90	CRI>90	30	3000K	IC	Ice	DA	DALI	CU	Custom	
			12	12W/m			40	4000K	CL	Clear	SW	Switch-Dim			
			16	16W/m			TW	2700K-6000K			CA	Casambi			
			14	14.4W/m			RGB	RGB			T2	Tunable White			
			20	19.2W/m											

# HAWKO Lighting reserve the right to change any data without notification \*\*See technical table for configurations