

18 SLIM RECESSED - H1809R




IP20

24V

5
YR
WARRANTY


TW




Key Features

- Complies with relevant Australian Standards
- Easy installation
- Butt joins to create longer lengths
- Supplied with all mounting components
- 45 & 90 bends available (custom bends available upon request)
- Remote Driver

Dimensions



Colour Options



Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

Code

Example: H1809R - R049027ODD079 - 2400

Code	Mounting		Power		CRI		CCT		Optics		Driver		Finish		Length
H1809R	R	Recessed	04 08 12 16 14 20	4W/m 8W/m 12W/m 16W/m 14.4W/m 19.2W/m	80 90	CRI>80 CRI>90	27 30 40 TW RGB	2700K 3000K 4000K 2700K-6000K RGB	OD Opal	DO DA SW CA T2	Non-Dim DALI Switch-Dim Casambi Tunable White	79 CU	Anodised Custom	- XXXX	

HAWKO Lighting reserve the right to change any data without notification