

60 ROUND - HE60T




Key Features

- Dot free illumination
- Easy installation
- Max module lengths are 2.5m
- Butt joins to create longer lengths
- 2m adjustable wire suspensions when suspending the luminaire
- Plastic fixed endcap

Dimensions

Profile



Colour Options



Technical Information

ECO FLEX G2											
IP20/IP67											
CRI>80											
Heatsink required for installation											
4.8W/m (5)			9.6W/m (10)			14.4W/m (15)			19.2W/m (20)		
2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K
500lm/m	520lm/m	575lm/m	1000lm/m	1050lm/m	1150lm/m	1530lm/m	1630lm/m	1730lm/m	2050lm/m	2150lm/m	2300lm/m

#See individual LED Flex data sheet for full break down

Code

Example:

H60T - S0590270DD011 - 2400

Code	Mounting		Power		CRI		CCT		Optics		Driver		Finish		Length
HE60T OR HE60TIP	S	Surface Mounted	5	4.8W/m	80	CRI>80	27	2700K	OD	Opal	DO	Non-Dim	79	Anodised	- XXXX
	P	Wire Pendant	10	9.6W/m			30	3000K			DA	DALI			
			15	14.4W/m			40	4000K			CA	Casambi			
			20	19.2W/m							PD	Phase Dim			

HAWKO Lighting reserve the right to change any data without notification