

CEILING MOUNTED LOW TRIM DOWNLIGHT (100 SERIES)



IP65


5 YR WARRANTY



Key Features

- 5 Year Warranty
- CRI>80 (Standard), CRI>90 (Optional)
- 220-240V
- Working Temperature: -20°c to +50°c
- 2mm thick toughened glass diffuser
- Aluminium housing with corrosion resistant powdercoating
- L80 >50000 hours

Dimensions



Technical Information

	Dimensions	Illumination	Lumens
	Width (W) x Height (H)	Wattage	Lumens/m
CML100120	100mm x 120mm	1x5	577
		1x10	1152
CML100150	100mm x 150mm	1x5	577
		1x10	1152
		1x15	1725
CML100200	100mm x 200mm	1x5	577
		1x10	1152
		1x15	1725

Code

Example: CML100120-1x5W-3K-80-B-ND-12

Fitting	Mounted		Illumination		LED Colour		CRI		Finish		Control Gear		Beam Angle	
CML100120 CML100150 CML100200	S	Surface Mounted	1x5W	1x5 Watts	3K	3000K	80	80	B	Black	ND	Non-Dim	12	12°
	P	Pendant	1x10W	1x10 Watts	4K	4000K	90	CRI>90	W	White	DA	DALI	24	24°
			1x15W	1x15 Watts	6K	6000K			G	Grey			36	36°
									M	Stainless Steel Mirror			60	60°
									BR	Stainless Steel Brushed				

# HAWKO Lighting reserve the right to change any data without notification