


H8850



Dimensions

Profile



Key Features

- Easy installation
- Max module lengths are 2.5m
- Butt joins to create longer lengths
- Remote Driver

Technical Information

	4.8W/m (5)	9.6W/m (10)	14.4W/m (15)	19.2W/m (20)	22W/m (22)
Monochrome	CCT 2700K / 3000K / 3500K / 4000K / 5000K / 6500K				
	Ingress Protection (IP) IP20				
	CRI> 90 / 95				
	Lumens/m (4000K)	425	850	1275	1700
RGB & SINGLE COLOURS	14.4W/m (14)				
	CCT RGB / Red / Green / Blue / Yellow				
	Ingress Protection (IP) IP20				
	CRI> -				
RGBW	19.2W/m (20)				
	CCT RGBW (3000K/4000K)				
	Ingress Protection (IP) IP20				
	CRI> -				
Tunable White	19.2W/m (19)		23W/m (23)		
	CCT 2500K-6000K				
	Ingress Protection (IP) IP20				
	CRI> 90				
Lumens/m		1680	1700		

Code

Example:

H8850-C-05-90--40-OP-DA-79-2500

Code		Mounting	Power		CRI		CCT		Optics		Driver		Finish		Length
H8850	H8850	C Cove	05	4.8W/m	90	CRI>90	27	2700K	OD	Opal	D0	Non-Dim	79	Natural	-XXXX
			10	9.6W/m	95	CRI>95	30	3000K			DA	DALI	CU	Anodised	
			14	14.4W/m			35	3500K			D4	DALI RGBW		Custom	
			15	14.4W/m			40	4000K			SW	Switch-Dim			
			19	19.2W/m			50	5000K			CA	Casambi			
			20	19.2W/m			65	6500K			C4	Casambi (TW/RGB/RGBW)			
			22	22W/m			TW	2500K-6000K				Tunable White (DALI/)			
			23	23W/m			RGB	RGB			T2				
							RGBW3K	RGBW 3000K							
							RGBW4K	RGBW 4000K							
							RGBW6K	RGBW 6000K							

FOS Lighting reserve the right to change any data without notification