

H60140



IP40

240V



*Cyanosis compliant on request




Key Features


- Complies with relevant Australian Standards
- Screwless end caps (On Request)
- Emergency Options available (On Request)
- Provided shop drawings
- Welded joints (On Request)
- Australian manufactured

Dimensions

Profile




Colour Options



Mounting

Wire Pendant (P) Up/Down Wire (U) Wall Up & Down Mounted (C) Wall Mounted (W)
Rod Pendant (D) Up/Down Rod (Y)



Code

Example:

H60140- P129030ODD010 - 2400

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length								
H60140	W	Wal Mounted	12	12 W/m	1008 lm/m	80	CRI>80	30	3000K	OD	Opal	DO	Non-Dim	10	Black	- XXXX
	C	Wall Up/Down	16	16 W/m	1344 lm/m	90	CRI>90	35	3500K	Lx	Linear Lens##	DA	DALI	11	White	
	P	Pendant (Wire)	20	20 W/m	1680 lm/m			40	4000K	Bx	Black	SW	Switch-Dim	75	Gray	
	D	Pendant (Rod)	24	24 W/m	2016 lm/m			50	5000K		Louvered##	CA	Casambi	CU	Custom	
	U	Pendant Up/Down (Wire)	28	28 W/m	2352 lm/m			TW	Tunable White	Wx	White	T2	Tunable White			
			32	32 W/m	2688 lm/m						Louvered##					
	Y	Pendant Up/Down (Rod)	36	36 W/m	3024 lm/m					TR	Tack					
			40	40 W/m	3360 lm/m					MS	Mini Spot					
										MP	Micro Prismatic Clear					

HAWKO Lighting reserve the right to change any data without notification ##Codes identified on the second page of the data sheet

Optics

Louvers



B8 - Black Wide 80°
B5 - Black Medium 50°
B3 - Black Narrow 35°
BO - Black Oval 25 + 70°
BA - Black Asymmetric
W8 - White Wide 80°
W5 - White Medium 50°
W3 - White Narrow 35°
WO - White Oval 25 + 70°
WA - White Asymmetric

Linear Lenses

*Not compatible with Tunable white configuration



L1 - Glare Control Lens 110°
L9 - Glare Control Lens 90°
L6 - Glare Control Lens 60°
L3 - Glare Control Lens 30°
LO - Glare Control Lens 30° + 60° Oval
LA - Glare Control Lens Asymmetric
LD - Glare Control Lens Double Asymmetric
LW - Glare Control Lens Wall Grazing

Opal Diffusers



OD - Opal Diffuser
MP - Micro Prismatic Clear

Track



TR - Track

Mini Spots



MS - Mini Spot