

18 RECESSED - HE1816R



IP20

24V

5
YR
WARRANTY


TW




Key Features

- Complies with relevant Australian Standards
- Easy installation
- Butt joins to create longer lengths
- Supplied with all mounting components
- 45 & 90 bends available (custom bends available upon request)
- Remote Driver

Dimensions



Colour Options



Technical Information

ECO FLEX G2											
IP20											
CRI>80											
Heatsink required for installation											
4.8W/m (5)			9.6W/m (10)			14.4W/m (15)			19.2W/m (20)		
2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K
500lm/m	520lm/m	575lm/m	1000lm/m	1050lm/m	1150lm/m	1530lm/m	1630lm/m	1730lm/m	2050lm/m	2150lm/m	2300lm/m

#See individual LED Flex data sheet for full break down

Code

Example: H1816R - R049027ODD079 - 2400

Code	Mounting		Power		CRI		CCT		Optics		Driver		Finish		Length
HE1816R	R	Recessed	5 10 15 20	4.8W/m 9.6W/m 14.4W/m 19.2W/m	80	CRI>80	27 30 40	2700K 3000K 4000K	OD IC CL	Opal Ice Clear	DO DA CA PD	Non-Dim DALI Casambi Phase Dim	79	Anodised	- XXXX

HAWKO Lighting reserve the right to change any data without notification