




## Key Features

- 5 Year Warranty
- CRI>97 (Standard), CRI>80 on request (3000K ONLY)
- IP20 (Standard), IP44 on request
- Honeycomb or frosted filter options

## Dimensions



## Technical Information

	Beam Angle	2700K CRI>97	3000K CRI>97	4000K CRI>97
9W	25°	650	654	738
	40°	659	650	728
	60°	634	626	703
11W	25°	850	895	990
	40°	871	891	987
	60°	839	904	971
15W	25°	1157	1209	1327
	40°	1145	1186	1322
	60°	1120	1206	1315
21W	25°	1569	1639	1820
	40°	1603	1686	1922
	60°	1488	1649	1776

## Code

Example: **Hyper 3.4-9W-B-27K-18-80-20-STD-HC**

Fitting	Wattage		Frame Colour		LED Colour		Beam Angle		CRI		IP		Dimming		Filters	
	9W	11W	B	W	27K	3000K	18	25	80	97	20	44	STD	Trailing & Leading Edge Dim (Standard)	HC	FR
Hyper 3.4	9W	11W	Black	White	2700K	3000K	18°	25°	CRI>80	CRI>97 (Standard)	IP20 (Standard)	IP44	DALI	DALI Dim	Honeycomb	Frosted
	15W	15W	Silver	Silver	4K	4000K	40°	60°								