

H7698HR




Key Features


- Easy installation
- Max module lengths are 3m
- Butt joins to create longer lengths
- Metal endcap

Dimensions

Profile



Colour Options



Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

Code

Example: **H7698HR -C-04-20-90-40-OD-D0-10-2500**

Code	Mounting	Power (Direct - Indirect)	CRI	CCT	Optics	Driver	Finish	Length
H7698HR	V76x98mm Hand Rail	W Wall Direct or Indirect C Wall Direct/ Indirect	04 4W/m 08 8W/m 12 12W/m 16 16W/m 14 14.4W/m 20 19.2W/m	90 CRI-90 95 CRI>95	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K 65 6500K TW 2500K-6000K RGB RGB RGBW3K RGBW 3000K RGBW4K RGBW 4000K RGBW6K RGBW 6000K	OD Opal T2 Tunable White (DALI)	10 Black 11 White 79 Natural CU Anodised Custom	-XXXX

FOS Lighting reserve the right to change any data without notification