

55 EDGE - H5580



IP20

240V

5
YR
WARRANTY


TW



Key Features

- Minimum length 600mm
- Maximum module length 4m
- 45°, 90°, T, X, Y bends available
- IP55 (On request)
- 2.9kg/m
- Custom colours available on request
- L80 B10 >100K Hours Lifetime

Dimensions



Colour Options

Anodic Natural
Matt (Gray)

White

Black

Custom

Mounting

- Surface Mounted (S)
- Wire Pendant (P)
Rod Pendant (D)
- Recessed Trimless (T)
- Wall Mounted (W)
Wall Mounted Adjustable (A)



Code

Example: H5580 - S168030ODDO11 - 2400

Code	Mounting		Power			CRI		CCT		Optics		Driver		Finish		Length
H5580	S	Surface Mounted	16	16W/m	1347 lm/m	80 90	CRI>80 CRI>90	30	3000K	OD MF	Opal Micro Prismatic Frosted	DO	Non-Dim	10 11 75 CU	Black White Gray Custom	- XXXX
	P	Wire Pendant	19	19 W/m	1761 lm/m			40	4000K			DA	DALI			
	D	Rod Pendant	26	26 W/m	2278 lm/m			50	5000K			PD	Push-Dim			
	T	Trimless Recessed	35	35 W/m	3004 lm/m			TW	2700K - 6500K			CA	Casambi			
	W	Fixed Wall	40	40W/m					TW			Tunable White				
	A	Adjustable wall														

HAWKO Lighting reserve the right to change any data without notification **Lumens based on 4000K ***CRI 80 as standard