

# 18 SQUARE - H1815




## Key Features


- Dot free illumination with 120 LED/m strips
- Easy installation
- Max module lengths are 2.5m
- Butt joins to create longer lengths
- 2 clear mounting clips per metre of extrusion
- 45 & 90 bends available (custom bends available upon request)
- Grey PMMA screwless end caps

## Dimensions

Profile



Mounting Bracket



## Colour Options



## Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

# Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

## Code

Example: **H1815 - S049027ODD079 - 2400**

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
H1815	S Surface Mounted	04 4W/m 08 8W/m 12 12W/m 16 16W/m 14 14.4W/m 20 19.2W/m	80 CRI>80 90 CRI>90	27 2700K 30 3000K 40 4000K TW 2700K-6000K RGB RGB	OD Opal IC Ice CL Clear	DO Non-Dim DA DALI SW Switch-Dim CA Casambi T2 Tunable White	79 Anodised CU Custom	- XXXX

# HAWKO Lighting reserve the right to change any data without notification