


HYPER 2.1



Key Features

- 5 Year Warranty
- CRI>90 or CRI>97
- IP20 (from below)
- Honeycomb or frosted filter options

Dimensions



Technical Information

LED Output	Module Output	Beam Angle	Height (H)	Diameter (D)	Cut Out	2700K CRI>97*	3000K CRI>97*	4000K CRI>97*
4W	5W	18°, 25°, 40°, 60°	60mm	93mm	80mm	418lm	428lm	474lm
9W	10W	18°, 25°, 40°, 60°	60mm	93mm	80mm	871lm	891lm	987lm
13W	15W	18°, 25°, 40°, 60°	60mm	93mm	80mm	1145lm	1186lm	1322lm
18W	20W	18°, 25°, 40°, 60°	80mm	93mm	80mm	1603lm	1686lm	1922lm

* Lumens based on 40 degree beam angle

Code

Example: **Hyper 2.1-4W-B-27K-18-90-STD-HC**

LED Output	Module Output	Frame Colour	LED Colour	Beam Angle	CRI	Dimming	Filters
Hyper 2.1	4W 9W 13W 18W	4W 9W 13W 18W	B Black W White S Silver	27K 2700K 3K 3000K 4K 4000K	18 18° 25 25° 40 40° 60 60°	90 CRI>90 97 CRI>97	STD Trailing & Leading Edge Dim (Standard) DALI DALI Dim HC Honeycomb FR Frosted

HAWKO Lighting reserve the right to change any data without notification