


# 18 RECESSED - H1816



## Features

- Max Module Distance: 2.5m
- Controls: Non-Dimmable, DALI Dimmable, Switch-Dim, Casambi, Tunable White
- Power Supply: Remote Driver
- Finish Colour: Natural Anodised, Black, White
- Installation Type: Recessed with 2 recessed brackets per metre
- Input Voltage: 24V


## Technical Information

	4W/m (04)	8W/m (08)	12W/m (12)	16W/m (16)	
Monochrome	CCT				
	2700K / 3000K / 3500K / 4000K				
	Ingress Protection (IP)				
	IP20				
RGB & SINGLE COLOURS	CCT				
	RGB / Red / Green / Blue / Yellow				
	Ingress Protection (IP)				
	IP20				
RGBW	CCT				
	RGBW (3000K/4000K/6000K)				
	Ingress Protection (IP)				
	IP20				
Tunable White	CCT				
	2500K-6000K				
	Ingress Protection (IP)				
	IP20				
Lumens/m		520	1000	1560	1800
Lumens/m		14.4W/m (14)			
Lumens/m		19.2W/m (19)*	19.2W/m (20)		
Lumens/m		410 (RGB)			
Lumens/m		920	920		
Lumens/m		19.2W/m (19)	23W/m (23)		
Lumens/m		1680	1700		

# HAWKO Lighting reserve the right to change any data without notification \*LED option has an on-board constant onrroller IC with inbuilt temperature control


## Accessories

### Mounting Bracket



## Photometrics

H1816R-R-10-90-40-OD-D0-79-1000



## Code

Example: **H1816R-R-04-90-27-OD-D0-79-2400**

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
H1815R	H1816R, IP20	R Recessed	90 CRI>90	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K 65 6500K TW 2700K-6000K RGB RGB RGBW3K RGBW 3000K RGBW4K RGBW 4000K RGBW6K RGBW 6500K	OD Opal	DO Non-Dim DA DALI D4 DALI RGBW SW Switch-Dim CA Casambi C4 Casambi ((TW, RGB, RGBW) T2 Tunable White	79 Natural Anodised 10 Black 11 WhiteCustom CU	-XXXX

# HAWKO Lighting reserve the right to change any data without notification