

H7698HR




Key Features


- Easy installation
- Max module lengths are 3m
- Butt joins to create longer lengths
- Metal endcap

Dimensions

Profile



Colour Options



Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

Code

Example: **H7698HR -C-04-20-90-40-OD-D0-10-2500**

Code		Mounting		Power (Direct - Indirect)		CRI		CCT		Optics		Driver		Finish		Length
H7698HR	V76x98mm Hand Rail	W	Wall Direct or Indirect	04	4W/m	90	CRI>90	27	2700K	OD	Opal	D0	Non-Dim	10	Black	- XXXX
		C	Wall Direct/ Indirect	08	8W/m	95	CRI>95	30	3000K			DA	DALI	11	White	
				12	12W/m			35	3500K			D4	DALI RGBW	79	Natural	
				16	16W/m			40	4000K			SW	Switch-Dim	CU	Anodised	
				14	14.4W/m			50	5000K			CA	Casambi		Custom	
				20	19.2W/m			65	6500K			C4	Casambi (TW/ RGB/RGBW)			
								TW	2500K-6000K			T2	Tunable White (DALI)			
								RGB	RGB							
								RGBW3K	RGBW 3000K							
								RGBW4K	RGBW 4000K							
								RGBW6K	RGBW 6000K							

FOS Lighting reserve the right to change any data without notification