

16 CORNER - H1616CR




Key Features


- Complies with relevant Australian Standards
- Easy installation
- Butt joins to create longer lengths
- Supplied with all mounting components
- 45 & 90 bends available (custom bends available upon request)
- Remote Driver

Dimensions

Profile



Mounting Bracket



Colour Options



Technical Information

X FLEX				COLOURFLEX	WHITEFLEX
2700K / 3000K / 4000K				RGB / Red / Green / Blue / Yellow	2500K-6000K
CRI>90					CRI>80
IP20				IP20	IP20
4W/m (4)	8W/m (8)	12W/m (12)	16W/m (16)	14.4W/m (14)	19.2W/m (20)
520lm/m	1040lm/m	1560lm/m	2080lm/m	350-410 (RGB)	1680lm/m
No heatsink required for installation				Heatsink required for installation	Heatsink required for installation

Lumens are based off 4000K values ##See individual LED Flex data sheet for full break down

Code

Example: **H1616CR - S049027ODD079 - 2400**

Code	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
H1616CR	S Surface Mounted	04 4W/m 08 8W/m 12 12W/m 16 16W/m 14 14.4W/m 20 19.2W/m	80 CRI>80 90 CRI>90	27 2700K 30 3000K 40 4000K TW 2700K-6000K RGB RGB	OD Opal	DO Non-Dim DA DALI SW Switch-Dim CA Casambi T2 Tunable White	79 Anodised CU Custom	- XXXX

HAWKO Lighting reserve the right to change any data without notification