

ZEUS -WALL MOUNT 80 SERIES


IP65

5 YR WARRANTY









Key Features

- 5 Year Warranty
- CRI>80 (Standard), CRI>90 (Optional)
- Direct, Indirect or Direct/Indirect options
- Fire resistant silicone seal waterproof gasket and 8mm toughened glass

Technical Information

	Dimensions	Driver Location	Illumination	Finish					Lumens @3000K			
	Width x Height			B	W	M	BR	G	12°	24°	36°	60°
WM80100	80mm x 100mm	Remote (DALI & Phase Dim) Intergral (Non-Dimming)	1x5W	-	-	-	-	-	465lm	460lm	455lm	450lm
			2x5W	-	-	-	-	-	930lm	920lm	910lm	900lm
			1x10W	-	-	-	-	-	930lm	920lm	910lm	900lm
			2x8W	-	-	-	-	-	1395lm	1380lm	1365lm	1350lm
WM80150	80mm x 150mm		1x5W	-	-	-	-	-	465lm	460lm	455lm	450lm
			2x5W	-	-	-	-	-	930lm	920lm	910lm	900lm
			1x10W	-	-	-	-	-	930lm	920lm	910lm	900lm
			2x8W	-	-	-	-	-	1395lm	1380lm	1365lm	1350lm
WM80200	80mm x 200mm	Integral (All control options)	1x5W	-	-	-	-	-	465lm	460lm	455lm	450lm
			2x5W	-	-	-	-	-	930lm	920lm	910lm	900lm
			1x10W	-	-	-	-	-	930lm	920lm	910lm	900lm
			2x8W	-	-	-	-	-	1395lm	1380lm	1365lm	1350lm

Code

Example: WM80100-1x5W-4K-80-R-B-ND-12

Fitting		Illumination		LED Colour		CRI		Shape		Finish		Control Gear		Beam Angle	
WM80100	Zeus Wall Mount 80mm x 100mm	1x5W 2x5W 1x10W	5W Direct 5W Direct, 5W Indirect 10W Direct	27K 3K 4K 5K	2700K 3000K 4000K 5000K	80 90	CRI>80 CRI>90	R S	Round Square	B W M BR G	Black White SS Mirrored SS Brushed Grey	ND DD PD	Non Dimmable DALI Dimmable Phase Dimming	12 24 36 60	12 24° 36° 60°
WM80150	Zeus Wall Mount 80mm x 150mm	1x5W 2x5W 1x10W 2x08W	5W Direct 5W Direct, 5W Indirect 10W Direct 8W Direct, 8W Indirect												
WM80200	Zeus Wall Mount 80mm x 200mm	1x5W 2x5W 1x10W 2x8W	5W Direct 5W Direct, 5W Indirect 10W Direct 8W Direct, 8W Indirect												

HAWKO Lighting reserve the right to change any data without notification