

36 PROUD - H3640




Key Features

- Easy installation
- Max module lengths are 2.9m
- Butt joins to create longer lengths
- 2m adjustable wire suspensions when suspending the luminaire
- 45 & 90 bends available (custom bends available upon request)
- Aluminium screwless end caps

Dimensions

Profile



Colour Options



Technical Information

ECO FLEX G2											
IP20/IP67											
CRI>80											
Heatsink required for installation											
4.8W/m (5)			9.6W/m (10)			14.4W/m (15)			19.2W/m (20)		
2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K	2700K	3000K	4000K
500lm/m	520lm/m	575lm/m	1000lm/m	1050lm/m	1150lm/m	1530lm/m	1630lm/m	1730lm/m	2050lm/m	2150lm/m	2300lm/m

#See individual LED Flex data sheet for full break down

Code

Example: **HE3640 - S059027ODD011 - 2400**

Code	Mounting		Power		CRI	CCT	Optics		Driver		Finish		Length
	S	P	5	10			OD	LED+	DO	DA	CA	PD	
HE3640		Surface Mounted	5	4.8W/m	80	CRI>80	27	2700K	-	-	-	-	-
OR		Wire Pendant	10	9.6W/m			30	3000K					
			15	14.4W/m			40	4000K					
HE3640IP			20	19.2W/m			60	6000K					

HAWKO Lighting reserve the right to change any data without notification