


ZEUS - WALL MOUNT 200 SERIES



Key Features

- 5 Year Warranty
- CRI>80 (Standard), CRI>95 (Optional)
- DALI-Dim Integrated driver only on profiles larger than 150mm
- Direct, Indirect or Direct/Indirect options
- Fire resistant silicone seal waterproof gasket and 8mm toughened glass

Dimensions



Technical Information

	Dimensions	Illumination	Finish					Lumens				
	Width x Height		Direction x Wattage	B	W	M	BR	G	12°	24°	36°	60°
VM200200	200mmx200mm	1x20W 1x30W 1x40W 1x60W 2x20W 2x30W 2x40W 2x60W	-	-				-	2448lm 3756lm 4876lm 7346lm 4886lm 7329lm 9784lm 14658lm	2349lm 3566lm 4633lm 7033lm 4672lm 7008lm 9342lm 14032lm	2234lm 3374lm 4478lm 6562lm 4459lm 6688lm 8922lm 13321lm	2127lm 3185lm 4270lm 6269lm 4247lm 6370lm 8495lm 12758lm
VM200300	200mmx300mm	1x20W 1x30W 1x40W 1x60W 2x20W 2x30W 2x40W 2x60W	-	-				-	2448lm 3756lm 4876lm 7346lm 4886lm 7329lm 9784lm 14658lm	2349lm 3566lm 4633lm 7033lm 4672lm 7008lm 9342lm 14032lm	2234lm 3374lm 4478lm 6562lm 4459lm 6688lm 8922lm 13321lm	2127lm 3185lm 4270lm 6269lm 4247lm 6370lm 8495lm 12758lm
VM200400	200mmx400mm	1x20W 1x30W 1x40W 1x60W 2x20W 2x30W 2x40W 2x60W	-	-				-	2448lm 3756lm 4876lm 7346lm 4886lm 7329lm 9784lm 14658lm	2349lm 3566lm 4633lm 7033lm 4672lm 7008lm 9342lm 14032lm	2234lm 3374lm 4478lm 6562lm 4459lm 6688lm 8922lm 13321lm	2127lm 3185lm 4270lm 6269lm 4247lm 6370lm 8495lm 12758lm
VM200600	200mmx600mm	2x20W 2x30W 2x40W 2x60W	-	-				-	4886lm 7329lm 9784lm 14658lm	4672lm 7008lm 9342lm 14032lm	4459lm 6688lm 8922lm 13321lm	4247lm 6370lm 8495lm 12758lm

Code

Example: WM200200-1x20W-3K-80-R-B-ND-12

Fitting	Illumination	LED Colour	CRI	Shape	Finish	Control Gear	Beam Angle
WM200200	200mm x 200mm	1x20W	1x20W Direct or Indirect	3K 3000K	80 CRI>80	R Round	B Black
WM200300	200mm x 300mm	1x30W	1x30W Direct or Indirect	4K 4000K	95 CRI>95	S Square	W White
WM200400	200mm x 400mm	1x40W	1x40W Direct or Indirect	5K 5000K			G Grey
VM200600	200mm x 600mm	1x60W	1x60W Direct or Indirect				
		2x20W	2x20W Direct/Indirect				
		2x30W	2x30W Direct/Indirect				
		2x40W	2x40W Direct/Indirect				
		2x60W	2x60W Direct/Indirect				
						ND Non-Dim	12 12°
						DD DALI-Dim	24 24°
							36 36°
							60 60°

FOS Lighting reserve the right to change any data without notification