





18 RECESSED

Profile



Mounting Clip



Construction Extruded recessed aluminium profile with acrylic diffuser

Finish Natural anodised, gloss/matt/mannex white, gloss/matt/mannex black powder coat (custom finishes available upon request)

Diffuser Clear, Ice or Opal

End Caps Grey PMMA screwless push on end caps

Mounting 2 x clear surface mounting clips per metre. Please note mounting clips are not specific recess clips and are designed to be surface mounted into rebates.

Bends Mitred 45°, 90° bends (custom bends available upon request)

Length Maximum 2.5mtr single piece lengths. Profile can be cut down onsite to suit specific applications. For longer runs, two or more lengths can be butt joined together to create seamless lengths.

| | ecoFLEX 4.8w/mtr | smoothFLEX 9.6w/mtr | starFLEX 14.4w/mtr | superFLEX 15w/mtr | powerFLEX 19.2w/mtr | hyperFLEX 21w/mtr | hyperFLEX+ 23w/mtr | colourFLEX 14w/mtr | chromaFLEX 23w/mtr |
|-----------------|---------------------|------------------------|-----------------------|----------------------|------------------------|----------------------|-----------------------|-----------------------|-----------------------|
| 18RECESSED IP20 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 18RECESSED IP67 | x | x | x | x | x | N/A | N/A | x | x |

