




20 D

Profile & Mounting Channel



Construction Extruded surface mount aluminium profile with round acrylic diffuser

Finish Natural anodised, gloss/matt/mannex white, gloss/matt/mannex black powder coat (custom finishes available upon request)

Diffuser Clear, Ice or Opal

End Caps Grey PMMA screwless push on end caps

Mounting Full length clip on mounting tray included. Mounting tray to be screw fixed prior to extrusion body being clipped in place.

Bends Mitred 45°, 90° bends (custom bends available upon request)

Length Maximum 2.5mtr single piece lengths. Profile can be cut down onsite to suit specific applications. For longer runs, two or more lengths can be butt joined together to create seamless lengths.

| | ecoFLEX 4.8w/mtr | smoothFLEX 9.6w/mtr | starFLEX 14.4w/mtr | superFLEX 15w/mtr | powerFLEX 19.2w/mtr | hyperFLEX 21w/mtr | hyperFLEX+ 23w/mtr | colourFLEX 14w/mtr | chromaFLEX 23w/mtr |
|----------|---------------------|------------------------|-----------------------|----------------------|------------------------|----------------------|-----------------------|-----------------------|-----------------------|
| 20D IP20 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 20D IP67 | ✓ | ✓ | ✓ | ✓ | ✓ | N/A | N/A | ✗ | ✗ |

