




hyperFLEX 21w/mtr



24v D.C. Input	L70 Lifetime
.IES Online	5 Year Warranty
3 Step MacAdam Ellipse	80 CRI

- Operating Temperature** -20 to +60 degree Celsius
- LED Type** Genuine Samsung 5630 CRI80 LED chips with 120 degree beam angle
- Construction** Flexible white double sided PCB with dense rolled copper for long life with 126 LED's spaced evenly per metre. IP20 strips come with easeCONNECT push fit connectors for cutting and joining. The strips come with genuine 3M #9495-300LSE double sided mounting tape.
- LED Colour/Efficacy** 2700K- 2550 lm/Mtr- Warmer White
3000K- 2650 lm/mtr- Warm White
4000K- 2767 lm/Mtr- Natural White
6000K- 2850 lm/Mtr- Pure White
- Cut Increment** Every 55.5mm
- IP Rating** IP20 Indoor Use Only

- LED Flex Length** Standard 5 Metre rolls
- LED Control** On-board intelligent constant current circuitry with built in temperature control. The intelligent constant current system ensures LED's run at a precise current even if slight fluctuations in input voltage occur, protecting and extending the life of the LED chips (unlike resistor based control). If the LED strip exceeds its maximum operating temperature, the integrated circuitry reduces the current to each LED chip until a safe operating temperature is reached.
- Lifetime** 70% lumen maintenance at 50,000 hours (L70 B10 >50,000hrs)
- Mounting** High quality 3M mounting tape. Maximum powered distance from tail at one end is 5mtrs. Hawko recommends no more than 1VDC volt drop between driver and the start of the LED strip. Detailed installation instructions available on our website.

